



***SUBLIMATION SOLUTION WITH 8 HEADS
UP TO 363 SQM/H OUTPUT***

Apsaras G5



Epson I3200



Industrial Feeder



Anti-Collision System



Efficient IR Dryer

| ITEM | SPECIFICATION | | | | | | | | | | | | |
|-----------------------|--|----------------------|-------------|----------------------|------------|-------------|----------------------|----------|--------------|----------------------|-------|--------------|----------------------|
| Model | Apsaras G5 | | | | | | | | | | | | |
| Print Head | 8 x Epson I3200 A1 Print Heads | | | | | | | | | | | | |
| Ink | GS High Density Sublimation Transfer Ink Certified by OEKO TEX with "ECO PASSPORT" | | | | | | | | | | | | |
| Color Config. | K.C.Y.M; Optional 8 colors: K.C.Y.M+ S1.S2.S3.S4 | | | | | | | | | | | | |
| Ink Supply System | Bulk Ink Supply System With Ink Cartridge | | | | | | | | | | | | |
| Printing Width | Up to 1950mm | | | | | | | | | | | | |
| Media Type | Transfer Paper(30 to 100gsm) | | | | | | | | | | | | |
| Feeder | Feeding: 2000m; Taking up: 1000m | | | | | | | | | | | | |
| Roll Diameter | Up to 350 mm | | | | | | | | | | | | |
| Drying System | Intelligent Sectionable Control IR Dryer | | | | | | | | | | | | |
| Printing Speed | <table border="1"> <tbody> <tr> <td>Draft</td> <td>720x600 dpi</td> <td>363m²/h</td> </tr> <tr> <td>Production</td> <td>720x600 dpi</td> <td>317m²/h</td> </tr> <tr> <td>High-res</td> <td>720x1200 dpi</td> <td>182m²/h</td> </tr> <tr> <td>Photo</td> <td>720x1200 dpi</td> <td>159m²/h</td> </tr> </tbody> </table> | Draft | 720x600 dpi | 363m ² /h | Production | 720x600 dpi | 317m ² /h | High-res | 720x1200 dpi | 182m ² /h | Photo | 720x1200 dpi | 159m ² /h |
| Draft | 720x600 dpi | 363m ² /h | | | | | | | | | | | |
| Production | 720x600 dpi | 317m ² /h | | | | | | | | | | | |
| High-res | 720x1200 dpi | 182m ² /h | | | | | | | | | | | |
| Photo | 720x1200 dpi | 159m ² /h | | | | | | | | | | | |
| Data Interface | External: USB 3.0; Internal: Fiber Optical | | | | | | | | | | | | |
| Working Environment | Temp.18°C~30°C; Humidity: 35%~65% | | | | | | | | | | | | |
| Software | NeoStampa Delta+GZ Printer Manager | | | | | | | | | | | | |
| Power | Single phase, 50Hz/AC, 220V±10%, Printer: 5.5A+ IR Dryer: 18A+28A | | | | | | | | | | | | |
| Packed/Installed Size | LxWxH(mm): 3760*1100*1940/4050*1280*1790 | | | | | | | | | | | | |
| G.W./ N.W. | 960kgs/ 705kgs | | | | | | | | | | | | |

***Specifications are liable to change without prior notice.**



8x Genuine Epson I3200 A1 Heads

8x staggered Epson I3200 print Heads deliver unparalleled productivity and high print quality. Optimized print head mounting plate for compact design and quick setup.



GZ Variable Dot Technology

GZ Variable Dot Technology delivers flawless skin tone, smoother gradient, crisp text and intricate detail without compromising speed.



Auto Capping & Wiping System

Self-developed auto capping station with particular slant-wiper save head maintenance time and extend head life.



Grooving Anti-Wrinkle Platen

Pressure adjustable pinch rollers, grooving platen and post spreading roller ensure wrinkle free media feeding, especially when printing dark colors.



Industrial Media Handle System

Heavy duty media handling system with unique stretchable rubber bar assures precise unwinding and rewinding; perfectly fit for low gram and jumbo roll paper.



Bulk Ink Supply System

Ink supply system with 5L ink tanks enables big volume output, easy maintenance and long-time unattended operation.



Ver 2024.07.22

Scan to watch video



@GONGZHENG GROUP

Authorized distributor:

Insight Print Communications Pvt Ltd.

A/14, Ground Floor, A Wing, Synthofine Industrial Estate,
B/H Virwani industrial Estate, C.T.S No.61, Plot No.2,
Dindoshi Off Aarey Road, Goregaon East,
Mumbai-400063.
Mob No. +91 99878 58599